

MOTB-C01 Termination Box

General Information

The termination box MOTB-C01 is designed for access of outdoor optical cable and drop cable with lockable protection from outdoor environment, specialty for FTTH, Telecommunication and CATV application.



Features:

- Construction-lightweight plastic offers strength •
- Resistance to chemical and U.V attack
- Wall mounting or pole mounting
- Available for SC and LC adapters
- Outdoor use IP 54
- Bend radius protection .
- Can hold 1:4 PLC Splitter
- Safety lock •

Application:

- Widely used in FTTH access network
- **Telecommunication Networks**
- **CATV** Networks
- Data communications Networks
- Local Area Networks

Technical specification:


Model	Cable port	Max. capacity of fiber splice	PLC splitter	Adaptors	Protection class
МОТВ-СО1	2 cable ports (for cables with max. diameter 12 mm)	4 splices	1:4 splitter	4x SC 4x DLC	IP 54

Physical parameters:

Weight: 0.55 kg Dimensions: $207 \times 152 \times 51.7$ (mm) Environmental temperature: -40°C ÷ +65°C



Ordering code:



1) WM = Standard accessories PM = Optional accessories - Item on request

Standard accessories:



Screw



screw



Buffering tube



Cable tie



Opened MOTB-C01 termination box



Closed MOTB-C01 termination box