

MOTB-X48A Termination Box

Description

The **MOTB-X48A** distribution box is designed to be used in distribution nodes of FTTH network, MDU building cabinet for example. It allows termination of optical cable by splicing of pigtails, including connection passive optical splitters 1:8, 1:16, 1:32 into passive fiber optic infrastructure. The ruggedized box is designed for both indoor and outdoor applications.

The **MOTB-X48A** box includes a holder for SC type coupling adapters and splice cassette for heat shrinkable or mechanical splice protection sleeves and holder for passive splitter. Provision for 2 optical fiber cables to enter and 12 smaller entries to leave the enclosure through weatherproof cable glands is provided. Outlet ports allow installation of 48 connectorized patchords.



Features

- Up to 48 drop cables
- Up to 54 simplex SC adapters
- Can accommodate up to 6 pieces 1x8, 1x16 and 1x32 PLC splitter
- Maximum capacity is 144 fibers (6 trays)
- The maximum capacity of splice trays is 24 fibers
- The oval port is for 1 loop cable or 2 cables with max Ø 20 mm
- The reserved port is for cables with max Ø 18 mm
- The twelve ports with diameter Ø 14 mm, each port can hold 4 drop cables
- Bending radius > 30 mm
- Environmental: Ingress Protection IP54
- Designed for Wall and Pole mount applications
- Safety lock
- Rugged and durable construction for long term reliability (UV resistance)
- Design for small and medium volumes of fiber optic cables
- Reusable
- RoHS compliance
- Dimensions: (L x W x H) 398 x 327 x 118 mm

Specification

Model No	Cable Port	Adaptors	PLC splitter
MOTB-X48A	The oval port is for 1 loop cable or 2 cables with max Ø 20 mm. The reserved port for cables with max Ø 18 mm The twelve ports with diameter Ø 14 mm, each port can hold 4 drop cables, totally 48 drop cables	54 SC adaptors	Up to 6 pieces 1x8, 1x16 or 1x32 PLC splitter

OPTOKON, a.s. reserves the right to make changes, without notice, to the products described in this document, in the interest of improving design, operational function and/or reliability. OPTOKON, a.s. reserves the right to make changes, without notice, to the products described in this document, in the interest of improving design, operational function and/or reliability. OPTOKON, a.s. creater and the changes of the products described in this document, in the interest of improving design, operational function and/or reliability. OPTOKON, a.s. creater and the changes of the products described in this document, in the interest of improving design, operational function and/or reliability. OPTOKON, a.s. creater and the products described in this document, in the interest of improving design, operational function and/or reliability.



Ordering code

MOTB -X48A	- XX - # of Adaptors Up to 54	- XX X ·		- (AA)		
			Adaptors Type		Optional	
		SC	SC	M Multimode		Accessories
		DLC	LC duplex	S Single mode	WM	Wall Mounting Kits ¹
				A APC	PM	Pole Mounting Kits ²
				X No adaptors		

Note:

WM = As standard accessories
PM = Item on request (Pole Mounting Kits)



MOTB-X48A-40-DLC S closed



MOTB-X48A-40-DLC S opened