



- DRP-240-48** Output 48VDC, 240W
- DR-120-48** Output 48VDC, 120W
- DR-120-24** Output 24VDC, 120W
- DR-4524** Output 24VDC, 45W
- MDR-40-24** Output 24VDC, 40W

Having reliable and stable power for your industrial grade converters is the best way to improve reliability and keep any down time to a minimum. CTC Union's safety certified AC to DC power supplies that are 100% compatible with all of our industrial grade switches and converters.

Feature

- The series of industrial grade power supply have been fully tested with our industrial product for guaranteed compatibility and performance
- Protections: Short circuit / Overload / Over voltage
- LED indicator for power on
- Cooling by free air convection
- Installation mounting by Din Rail
- UL508, UL60950-1, CE approved
- Heavy industry grade EMS EN61000-6-2 approved
- 3 years warranty

Specifications

Model Name		DRP-240-48	DR-120-48	DR-120-24
Output	Dc Voltage	48V	48V	24V
	Rated Current	5A	2.5A	5A
	Current Range	0~5A	0~2.5A	0 ~ 5A
	Rated Power	240W	120W	120W
	Output Voltage Adj. Range	48 ~ 53VDC	48~53VDC	24 ~ 28VDC
Input	Voltage Range	85 ~ 264VAC / 120 ~ 370VDC	88 ~ 132VAC / 176 ~ 264VAC, 248 ~ 370VDC by switch	88 ~ 132VAC / 176 ~ 264VAC, 248 ~ 370VDC by switch
	Frequency Range	47 ~ 63Hz	47 ~ 63Hz	47 ~ 63Hz
	Efficiency (Typ.)	85%	85%	84%
Protection	Overload	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	Over Voltage	54 ~ 60V Protection type : Shut down o/p voltage, re-power on to recover	58~65V Protection type : Shut down o/p voltage, re-power on to recover	29 ~ 33V Protection type : Shut down o/p voltage, re-power on to recover
Alarm Relay	DC OK Relay			
Indicator	LED	Power On	Power On	Power On
Housing	Dimension	100 x 125.5 x 125.2 mm (D x W x H)	100 x 65.5 x 125.2mm (D x W x H)	100 x 65.5 x 125.2mm (D x W x H)
	Installation Mounting	DIN Rail	DIN Rail	DIN Rail
Environment	Working Temp	-10 ~ 70°C	-10 ~ 60°C	-10 ~ 60°C
	Working Humidity	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-20 ~ 85°C , 10 ~ 95% RH	-40 ~ 85°C , 10 ~ 95% RH	-20 ~ 85°C , 10 ~ 95% RH
	Vibration	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6
Safety & EMC	Safety Standards	UL508, UL60950-1 approved	UL508, UL60950-1 approved	UL508, UL60950-1 approved
	EMC Emission	Compliance to EN55011, EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2, -3	Compliance to EN55011, EN55022 (CISPR22) Class B, EN61000-3-2,-3	Compliance to EN55011, EN55022 (CISPR22) Class B, EN61000-3-2,-3
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, (EN50082-2), heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2 (EN50082-2) heavy industry level, criteria A
Others	PFC	Built in Active PFC		
	MTBF	289.9K hrs MIL-HDBK-217F (25°C)	432.1Khrs MIL-HDBK-217F (25°C)	432.1Khrs MIL-HDBK-217F (25°C)
	Waranty	3 Years	3 Years	3 Years

Model Name		DR-4524	MDR-40-24
Output	Dc Voltage	24V	24V
	Rated Current	2A	1.7A
	Current Range	0 ~ 2A	0 ~ 1.7A
	Rated Power	48W	40.8W
	Output Voltage Adj. Range	21.6 ~ 26.4VDC	24 ~ 30VDC
Input	Voltage Range	85 ~ 264VAC / 120 ~ 370VDC	85 ~ 264VAC / 120 ~ 370VDC
	Frequency Range	47 ~ 63Hz	47 ~ 63Hz
	Efficiency (Typ.)	80%	88%
Protection	Overload	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	Over Voltage	27.6 ~ 32.4V Protection type : Shut off o/p voltage, clamping by zener diode	31.2 ~ 36V Protection type : Shut down o/p voltage, re-power on to recover
Alarm Relay	DC OK Relay		DC OK Relay will Close In Normal Relay contact rating(max.) : 30V/1A resistive
Indicator	LED	Power On	DC OK
Housing	Dimension	67 x 78 x 93 mm (D x W x H)	100 x 40 x 90 mm (D x W x H)
	Installation Mounting	DIN Rail	DIN Rail
Environment	Working Temp	-10 ~ 50°C	-20 ~ 70°C
	Working Humidity	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-20 ~ 85°C , 10 ~ 95% RH	-40 ~ 85°C , 10 ~ 95% RH
	Vibration	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6
Safety & EMC	Safety Standards	UL508 approved	UL508, UL60950-1 approved
	EMC Emission	Compliance to EN55011, EN55022 (CISPR22) Class B, EN61000-3-2,-3	Compliance to EN55011, EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2,-3
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2 (EN50082-2), heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A
Others	PFC		
	MTBF	364.6K hrs MIL-HDBK-217F (25°C)	301.7K hrs MIL-HDBK-217F (25°C)
	Waranty	3 Years	3 Years

Ordering Information

Model Name	Input AC Voltage Range	Output Voltage	Output Voltage Adj. Range	Output Power	Operating Temperature
DRP-240-48	85~264VAC	48VDC	48~53V	240W	-10 ~ +70 C
DR-120-48	"88~132VAC, 176~264VAC"	48VDC	48~53VDC	120W	-10 ~ +50 C
DR-120-24	"88~132VAC, 176~264VAC"	24VDC	24 ~ 28V	120W	-10 ~ +50 C
DR-4524	85~264VAC	24VDC	21.6 ~ 26.4V	45W	-10 ~ +50 C
MDR-40-24	85~264VAC	24VDC	24 ~ 30V	40W	-20 ~ +70 C